SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

BIKE7 PROTECT AND SHINE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : BIKE7 PROTECT AND SHINE Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Lubricating oil

Detergent according to Regulation (EC) No 648/2004

1.2.2 Uses advised against

No uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

BIKE 7*

Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

₼ +32 14 85 97 38

info@tec7.be

*BIKE 7 is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

4 +32 14 85 97 38

info@tec7.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.

2.2. Label elements



Signal word Danger

H-statements

Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

P-statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

http://www.big.be

© BIG vzw

Reason for revision: 8; 15

Revision number: 0604

Publication date: 2008-03-20 Date of revision: 2019-11-22 134-17438-677-en

Product number: 44875 1 / 13

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
white mineral oil (petroleum) 01-2119487078-27	8042-47-5 232-455-8	15% <c<30%< td=""><td>Asp. Tox. 1; H304</td><td>(1)(2)(10)</td><td>Constituent</td></c<30%<>	Asp. Tox. 1; H304	(1)(2)(10)	Constituent
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119457273-39		15% <c<30%< td=""><td>Asp. Tox. 1; H304</td><td>(1)(10)</td><td>Constituent</td></c<30%<>	Asp. Tox. 1; H304	(1)(10)	Constituent
propane 01-2119486944-21	74-98-6 200-827-9		Flam. Gas 1; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant
butane 01-2119474691-32	106-97-8 203-448-7	C>30 %	Flam. Gas 1; H220 Press. Gas - Liquefied gas;	(1)(2)(10)(21)	Propellant

⁽¹⁾ For H-statements in full: see heading 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Rinse with water. Do not apply (chemical) neutralizing agents without medical advice. Take victim to a doctor if irritation persists.

After eye contact:

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply (chemical) neutralizing agents without medical advice. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Do not induce vomiting. Do not apply (chemical) neutralizing agents without medical advice. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

No effects known.

After skin contact:

No effects known.

After eye contact:

Redness of the eye tissue.

After ingestion:

Headache. Vomiting. Diarrhoea. Abdominal pain. Drowsiness.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion.

5.3.2 Special protective equipment for fire-fighters:

Reason for revision: 8; 15 Publication date: 2008-03-20
Date of revision: 2019-11-22

Revision number: 0604 Product number: 44875 2 / 13

⁽²⁾ Substance with a Community workplace exposure limit

⁽¹⁰⁾ Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

^{(21) 1,3-}butadiene < 0.1%

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: compressed air apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosion proof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Protect against frost. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Belgium

Huiles minérales (brouillards)	Time-weighted average exposure limit 8 h	5 mg/m³
	Short time value	10 mg/m ³
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm
	Short time value	980 ppm
	Short time value	2370 mg/m ³
	•	

The Netherlands

Olienevel (minerale olie)	Time-weighted average exposure limit 8 h (Public occupational exposure 5 mg/m ³	
	limit value)	
		-

France

	Trance		
n-Butane		Time-weighted average exposure limit 8 h (VL: Valeur non	800 ppm
		réglementaire indicative)	
		Time-weighted average exposure limit 8 h (VL: Valeur non	1900 mg/m ³
		réglementaire indicative)	

Germany

Reason for revision: 8; 15 Publication date: 2008-03-20 Date of revision: 2019-11-22

Revision number: 0604 Product number: 44875 3 / 13

Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900) 2400	
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m³
Weißes Mineralöl (Erdöl)	Time-weighted average exposure limit 8 h (TRGS 900)	5 mg/m³

UK

			
		Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
		Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m³
		Short time value (Workplace exposure limit (EH40/2005))	750 ppm
		Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m ³

USA (TLV-ACGIH)

Butane, all isomers	Short time value (TLV - Adopted Value)	1000 ppm
Mineral oil, pure, highly and severely refined	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m³ (I)

⁽I): Inhalable fraction

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

Product name	Test	Number
Oil Mist (Mineral)	NIOSH	5026

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

white mineral oil (petroleum)

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	164.56 mg/m³	
	Long-term systemic effects dermal	217.05 mg/kg bw/day	

DNEL/DMEL - General population

white mineral oil (petroleum)

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	34.78 mg/m ³	
	Long-term systemic effects dermal	93.02 mg/kg bw/day	
	Long-term systemic effects oral	25 mg/kg bw/day	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

	Measured breakthrough time	Remark	Protection index
nitrile rubber	> 480 minutes	0.35 mm	Class 6

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol			
Odour	Characteristic odour			
Odour threshold No data available in the literature				
Colour	No data available on colour			
Particle size	Not applicable (aerosol)			
Explosion limits	0.7 - 9.5 vol % ; Propellant			
Flammability	Extremely flammable aerosol.			

Reason for revision: 8; 15 Publication date: 2008-03-20 Date of revision: 2019-11-22

 Revision number: 0604
 Product number: 44875
 4 / 13

Log Kow	Not applicable (mixture)
Dynamic viscosity	1 mPa.s ; 20 °C ; Liquid
Kinematic viscosity	1 mm²/s ; 40 °C ; Liquid
Melting point	No data available in the literature
Boiling point	No data available in the literature
Evaporation rate	0.04 ; Butyl acetate ; Liquid
Relative vapour density	> 1
Vapour pressure	8530 hPa; 20 °C; Propellant
Solubility	Water ; insoluble
Relative density	0.81 ; 20 °C ; Liquid
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	61 °C ; Liquid
	Not applicable (aerosol)
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
рН	No data available in the literature

9.2. Other information

Alexa listeral assates	040 1-7-3 - 20 % - 1554
Absolute density	810 kg/m³ ; 20 °C ; Liquid

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Unstable on exposure to heat.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

BIKE7 PROTECT AND SHINE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

white mineral oil (petroleum)

Route of exposure	Parameter	Method	Value	Exposure time		Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw			Read-across	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5 mg/l	4 h	Rat (male / female)	Read-across	

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD	> 5000 mg/kg bw		Rat (male /	Read-across	
		401			female)		
Dermal	LD50	Equivalent to OECD	> 3160 mg/kg bw	24 h	Rabbit (male /	Read-across	
		402			female)		
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5.6 mg/l	4 h	Rat (male)	Read-across	

Conclusion

Not classified for acute toxicity

Reason for revision: 8; 15 Publication date: 2008-03-20 Date of revision: 2019-11-22

Revision number: 0604 Product number: 44875 5 / 13

Corrosion/irritation

BIKE7 PROTECT AND SHINE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

white mineral oil (petroleum)

F	Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
	Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit		Single treatment without rinsing
[Skin	Not irritating	Equivalent to OECD 404	24 week(s)	24; 72 hours	Rabbit	Read-across	

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Not irritating	OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

Conclusion

Not classified as irritating to the skin Not classified as irritating to the eyes

Respiratory or skin sensitisation

BIKE7 PROTECT AND SHINE

No (test)data on the mixture available

Judgement is based on the relevant ingredients white mineral oil (petroleum)

Route of exposure	Result	Method		Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD	24 week(s)	48 hours	Guinea pig	Read-across	
		406			(male)		

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method		Species	Value determination	Remark
			point			
Skin	Not sensitizing	Equivalent to OECD	24; 48 hours	Guinea pig	Read-across	
		406		(female)		

Conclusion

Not classified as sensitizing for skin Not classified as sensitizing for inhalation

Specific target organ toxicity

BIKE7 PROTECT AND SHINE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

white mineral oil (petroleum)

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (diet)	NOAEL	OECD 453	≥ 1200 mg/kg bw/day		No effect	24 month(s)	Rat (male / female)	Read-across
Dermal	NOAEL systemic effects	OECD 411	≥ 2000 mg/kg bw/day		No adverse systemic effects	13 weeks (daily)	Rat (male / female)	Read-across
Inhalation (aerosol)	NOEL	Equivalent to OECD 412	50 mg/m ³	Lungs		4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 422	≥ 1000 mg/kg bw/day		No effect		Rat (male / female)	Read-across
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	≥ 2200 mg/m³ air			14 weeks (6h / day, 5 days / week)	Rat (female)	Read-across

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

BIKE7 PROTECT AND SHINE

No (test)data on the mixture available Judgement is based on the relevant ingredients

Reason for revision: 8; 15 Publication date: 2008-03-20 Date of revision: 2019-11-22

Revision number: 0604 Product number: 44875 6/13

white mineral oil (petroleum)

R	tesult	Method	Test substrate	Effect	Value determination	Remark
Ν	Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	

<u>hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics</u>

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	
activation, negative					
without metabolic					
activation					

Mutagenicity (in vivo)

BIKE7 PROTECT AND SHINE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

white mineral oil (petroleum)

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	OECD 474		Mouse (male / female)	Bone marrow	Read-across

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD		Rat (male)		Read-across
	478				

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

BIKE7 PROTECT AND SHINE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

white mineral oil (petroleum)

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
exposure								determination
Dermal	NOEL	OECD 453	≥ 75 µl/week	104 weeks (3 times / week)	Mouse (male)	No carcinogenic effect		Read-across
Oral	NOAEL	OECD 453	≥ 1200 mg/kg bw/day	24 month(s)	Rat (male / female)	No carcinogenic effect		Read-across

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
exposure								determination
Inhalation	NOAEC	Equivalent to	≥ 2200 mg/m³	105 weeks (6h / day,	Rat (female)	No carcinogenic		Read-across
(vapours)		OECD 453	air	5 days / week)		effect		

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

BIKE7 PROTECT AND SHINE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

white mineral oil (petroleum)

ree minierar on (petrolean	4							
	Parameter	Method	Value	Exposure time	Species	Effect	1- 0-	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	> 5000 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect		Read-across
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	> 5000 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect		Read-across
Effects on fertility (Dermal)	NOAEL	Equivalent to OECD 415	≥ 2000	≥ 13 weeks (5 days / week)	Rat (male / female)	No effect		Read-across

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	1						i e	i
	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
								determination
Developmental toxicity	NOAEC		≥ 1575 mg/m³	10 days (6h / day)	Rat (female)	No effect		Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	≥ 5220 mg/kg	10 day(s)	Rat	No effect		Experimental value

Conclusion

Not classified for reprotoxic or developmental toxicity

Reason for revision: 8; 15 Publication date: 2008-03-20 Date of revision: 2019-11-22

Revision number: 0604 Product number: 44875 7 / 13

Toxicity other effects

BIKE7 PROTECT AND SHINE

No (test)data on the mixture available

<u>hydrocarbons</u>, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
							determination
			Skin	Skin dryness or			Literature study
				cracking			Skin

Chronic effects from short and long-term exposure

BIKE7 PROTECT AND SHINE

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

BIKE7 PROTECT AND SHINE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

white mineral oil (petroleum)

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 100 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	LC50	OECD 202	> 100 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	NOEL	OECD 201	≥ 100 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Weight of evidence; Growth rate
Long-term toxicity fish	NOEL		≥ 1000 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR
Long-term toxicity aquatic crustacea	NOEL	Equivalent to OECD 211	10 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Read-across; GLP

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Duration	Species	_		Value determination
Acute toxicity fishes	LL50	OECD 203	> 1000 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	> 1000 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	NOELR	OECD 201	> 1000 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system		Experimental value; GLP
Toxicity aquatic micro- organisms	EL50		> 1000 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

white mineral oil (petroleum)

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	31 %; GLP	28 day(s)	Read-across

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination	
AOPWIN v1.90	0.1 day(s) - 0.6 day(s)	1500000 /cm³	Calculated value	

Biodegradation soil

ouegradation son					
Method	Value	Duration	Value determination		
			Data waiving		

Reason for revision: 8; 15 Publication date: 2008-03-20 Date of revision: 2019-11-22

Revision number: 0604 Product number: 44875 8 / 13

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	80 %; GLP	28 day(s)	Read-across

Biodegradation soil

Method	Value	Duration	Value determination
Equivalent or similar to OECD 304A	59.7 % - 62.6 %; Oxygen	61 day(s)	Read-across
	consumption		

Conclusion

Contains non readily biodegradable component(s)

The surfactant(s) is/are biodegradable according to Regulation (EC) No 648/2004

12.3. Bioaccumulative potential

BIKE7 PROTECT AND SHINE

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

white mineral oil (petroleum)

BCF fishes

P	Parameter	Method	Value	Duration	Species	Value determination
						Data waiving

Log Kow

Method	Remark	Value	Temperature	Value determination
		> 6		Calculated

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

white mineral oil (petroleum)

(log) Koc

Parameter	Method	Value	Value determination
			Data waiving

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Percent distribution

Method	Fraction air		Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	65.8 %	0 %	22.9 %	9.6 %	1.7 %	Calculated value

Conclusion

Contains component(s) that adsorb(s) into the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

BIKE7 PROTECT AND SHINE

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

white mineral oil (petroleum)

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Reason for revision: 8; 15 Publication date: 2008-03-20

Date of revision: 2019-11-22

Revision number: 0604 Product number: 44875 9 / 13

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

13 02 05* (waste engine, gear and lubricating oils: mineral-based non-chlorinated engine, gear and lubricating oils).

20 01 29* (separately collected fractions (except 15 01): detergents containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Packing group

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road	(ADR)	
14.	1. UN number	
	UN number	1950
	2. UN proper shipping name	
	Proper shipping name	Aerosols
14.	3. Transport hazard class(es)	
	Hazard identification number	
	Class	2
	Classification code	5F
14.	4. Packing group	
	Packing group	
	Labels	2.1
14.	5. Environmental hazards	
	Environmentally hazardous substance mark	no
14.	6. Special precautions for user	
	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	1	liquids. A package shall not weigh more than 30 kg. (gross mass)
Rail (•	
14.	1. UN number	
	UN number	1950
	2. UN proper shipping name	
	Proper shipping name	Aerosols
14.	3. Transport hazard class(es)	
	Hazard identification number	23
	Class	2
	Classification code	5F
14.	4. Packing group	
	Packing group	
	Labels	2.1
14.	5. Environmental hazards	
	Environmentally hazardous substance mark	no
14.	6. Special precautions for user	
	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
Inlan	d waterways (ADN)	
14.	1. UN number	
	UN number	1950
14.	2. UN proper shipping name	
	Proper shipping name	Aerosols
14.	3. Transport hazard class(es)	
	Class	2
	Classification code	5F
14.	4. Packing group	
	Dealing group	

Reason for revision: 8; 15 Publication date: 2008-03-20 Date of revision: 2019-11-22

Revision number: 0604 Product number: 44875 10 / 13

Labels	2.1
14. <u>5. Environmental hazards</u>	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass)
a (IMDG/IMSBC)	
14.1. UN number	
UN number	1950
14.2. UN proper shipping name	-
Proper shipping name	aerosols
14.3. Transport hazard class(es)	•
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Transport in bulk according to Annex II of Marpol and the IBC Cod	
Annex II of MARPOL 73/78	Not applicable
(ICAO-TI/IATA-DGR)	•
14.1. UN number	1050
UN number	1950
14.2. UN proper shipping name	Agracals flammable
Proper shipping name 14.3. Transport hazard class(es)	Aerosols, flammable
Class	2.1
	2.1
14.4. Packing group	
Packing group	2.4
Labels	2.1
14.5. Environmental hazards	In.
Environmentally hazardous substance mark	no
14.6. Special precautions for user	A1 4F
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	

SECTION 15: Regulatory information

Limited quantities: maximum net quantity per packaging

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture <u>European legislation:</u>

VOC content Directive 2010/75/EU

VOC content	Remark
83.800 %	
542.379 g/l	

30 kg G

Ingredients according to Regulation (EC) No 648/2004 and amendments

 \geq 30% aliphatic hydrocarbons, <5% anionic surfactants, perfumes, limonene, cinnamal European drinking water standards (Directive 98/83/EC)

Reason for revision: 8; 15 Publication date: 2008-03-20

Date of revision: 2019-11-22

Revision number: 0604 Product number: 44875 11 / 13

white mineral oil (petroleum)

Parameter	Parametric value	Note	Reference	
Pesticides	0.1 μg/l		Listed in Annex I, Part B, of Directive 98/83/EC on the quality of water intended for human consumption.	
Pesticides — Total	0.5 μg/l		Listed in Annex I, Part B, of Directive 98/83/EC on the quality of water intended for human consumption.	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· white mineral oil (petroleum) · hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010. 6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the pre

National legislation Belgium BIKE7 PROTECT AND SHINE

No data available

National legislation The Netherlands BIKE7 PROTECT AND SHINE

Waterbezwaarlijkheid Z (2); Algemene Beoordelingsmethodiek (ABM)

National legislation France

BIKE7 PROTECT AND SHINE

No data available

National legislation Germany BIKE7 PROTECT AND SHINE

	WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017		
white mineral oil (petroleum)				
	TA-Luft	5.2.5/I		
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	TA-Luft	5.2.5		

National legislation United Kingdom BIKE7 PROTECT AND SHINE

No data available

Other relevant data
BIKE7 PROTECT AND SHINE

No data available

white mineral oil (petroleum)

TLV - Carcinogen Mineral oil, pure, highly and severely refined; A4

15.2. Chemical safety assessment

Reason for revision: 8; 15 Publication date: 2008-03-20

Date of revision: 2019-11-22

Revision number: 0604 Product number: 44875 12 / 13

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H-statements referred to under heading 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

(*) INTERNAL CLASSIFICATION BY BIG

ADI Acceptable daily intake

AOEL Acceptable operator exposure level

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 %

LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration
STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 8; 15 Publication date: 2008-03-20 Date of revision: 2019-11-22

Revision number: 0604 Product number: 44875 13 / 13