

Freewheels MTB

Model No.	MFM56 8CV	MFM4S 7CV	MFM30 7CS	MFM3S 7CS	MFM20 6DS
Speeds	8-Speed	7-Speed	7-Speed	7-Speed	6-Speed
Lock Ring Type	•	•	•	•	X
Function	Fluid Drive™	Fluid Drive Plus™	Fluid Drive Plus™	Fluid Drive Plus™	Fluid Drive Plus™
Number of Teeth	13-34T	13-34T	13-28T	13-28T	14-28T
Gear Combination	13-15-17-19-21-24-28-34	13-15-17-19-21-24-34	13-15-17-19-21-24-28	13-15-17-19-21-24-28	14-16-18-21-24-28
Sprocket Finish	(U) Zinc + EDB	(U) Zinc + EDB	(C) Chrome Plated	(U) Zinc Plated	(U) Zinc Plated
Sprocket Material	Steel	Steel	Steel	Steel	Steel
Light Weight Holes	X	•	•	•	•
Spacer Material	Engineering Polymers				
Chain Compatibility	7.1~7.3mm	7.3mm	7.3mm	7.3mm	7.3~7.8mm
Average Weight	609g	504g	460g	460g	433g

Freewheels MTB

Model No.	MFM2A 7DV	MFM2A 7CS	MFM2A 7DS	MFM2A 6DS	MFM2A 5DS	MFM05 7DS	MFM05 6DS	MFM05 5DS
Speeds	7-Speed	7-Speed	7-Speed	6-Speed	5-Speed	7-Speed	6-Speed	5-Speed
Lock Ring Type	•	•	•	•	•	X		
Function	Fluid Drive™	Fluid Drive™	Fluid Drive™	Fluid Drive™	Fluid Drive™	Friction		
Number of Teeth	14-34T	13-28T	14-28T	14-28T	14-28T	14-28T	14-28T	14-28T
Gear Combination	14-16-18-20-22-24-34	13-15-18-20-22-24-28	14-16-18-20-22-24-28	14-16-18-21-24-28	14-16-20-24-28	14-16-18-20-22-24-28	14-16-18-20-24-28	14-16-20-24-28
Sprocket Finish	(3) Zinc+EDB (2) Brown+EDB	(1) Zinc	(1) Zinc (2) Brown+EDB	(1) Zinc (2) Brown+EDB	(1) Zinc (2) Brown+EDB	(B) Black		
Sprocket Material	Steel					Steel		
Spacer Material	Engineering Polymers					Engineering Polymers		
Chain Compatibility	7.3mm	7.3mm	7.3mm	7.3~7.8mm	7.8mm	7.3mm	7.3~7.8mm	7.8mm
Average Weight	535g	479g	495g	458g	416g	480g	468g	432g