

Technical Data Sheet

Podium sealant

More properties: General Description

World's most advanced tire flats prevention fluid.

Properties

Sealant for professional XC, Enduro, DH, Gravity and Trail riders that demand ultra-high performance from their sealant.

Seals holes and cuts Instantly - up to 10mm.

Designed specifically for tubeless ready tires in tough conditions. More properties:

- CO₂ compatible.
- Prevents air leaks from thin tire side walls.
- Up to 300km - ultra high performance. 100-300 km high performance. 1000km and up - Standard performance (as Eco/Super Sealant).
- Compatible with a wide range of temperatures (-5°C - +50°C).
- Compatible with a wide range of pressures (15PSI - 100PSI).
- Store in a cool dry place out of direct sunlight.
- One bottle (125ml) is good for one wheel.

The performance may vary according to tire type.

Working Instructions

Refer to the MSDS before using this product.

1. Remove the valve core and bottle's cap.
2. Block spout's end with finger.
3. SHAKE WELL and apply immediately through the valve, while the valve is at 8 o'clock position
4. Squeeze bottle to fill in the sealant.
5. Close the valve core tightly and inflate air into the wheel.
6. Rotate wheel while shaking side ways

Cleaning Instructions

1. Hands and tools cleaning is performed using soap and water immediately after use. After drying, the product can be cleaned with Sealant Remover and rinse with water.

Technical Properties

Property	Value
Based	Natural / Synthetic Rubber
Color	white
pH	10.5-11.5
Viscosity	7-8 (cP) Spi-1/v-100
Density	1.0-1.03 (g/cm ³)
Shelf Life	3 years
Pot Life	3-6 months, depending on terms of storage
Packing	120 ml bottle
Storage	In a cold, dry place
Dilution and Cleaning	Soap and water immediately after use. After drying, Sealant Remover and rinse with water
Hands cleaning	Soap and water immediately after use. After drying, Sealant Remover and rinse with water

September 2023

Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of this product for your particular purposes prior to use. No warranties of any kind are made regarding products described or designs, data or information set forth. Adhestick Innovations Ltd. assumes no obligation or liability for the description, designs, data and information given or results obtained, all such being given and accepted at your risk.

ADHESTICK INNOVATIONS LTD.

17 Hamelacha St., P.O.Box 11675, Afek Industrial Park, Rosh Ha'ain 4809144, Israel
 Tel. +972 3 9027080 | Fax. +972 3 9027077 | Vat 515274389
 info@adhestick.com