

# Technical Data Sheet



## Joe's Elite Racer's Sealant

Office: +972-3-9027080  
 Fax: +972-3-9027077  
 17 Hamelacha St.  
 Rosh Ha'ain 4809144, Israel

+972-3-9027080 :משרד  
 +972-3-9027077 :פקס  
 17 המלאכה רח'  
 ראש העין 4809144, ישראל

Adhestick Innovations Ltd.  
 adhestick.com



### General Description

Tire flats prevention fluid for professional field cyclists.

### Properties

Quick response tire flats prevention fluid. Developed especially for professional cyclists and competitors, in order to immediately seal holes up to 6 mm depth.

### Working Instructions

1. Refer to the MSDS before using this product.
- 125 ml bottle installation instructions:
  1. Remove the valve core and bottle's cap.
  2. Block spout's end with finger.
  3. Shake well and apply immediately through the valve, while at 8 o'clock position.
  4. Squeeze bottle to fill in desired amount of sealant.
  5. Close the valve core tightly and inflate air into the wheel.
  6. Rotate wheel while shaking side ways to spread the sealant.
- 0.5 L bottle installation instructions:
  1. Remove the valve core and bottle's cap.
  2. Shake well and immediately squeeze desired amount into application bottle.
  3. Block application spout end with finger.
  4. Shake well and immediately insert application spout on to valve at 8 o'clock position.
  5. Squeeze application bottle to fill in the desired amount of sealant.
  6. Replace the valve core & inflate air into the wheel.
  7. Rotate wheel while shaking side ways to spread the sealant

### Cleaning Instructions

1. Hands and tools cleaning is performed using soap and water immediately after use. After drying, the product can be cleaned with Sealant Remover and rinse with water.

### Technical Properties

Property	Value
Based	Natural / Synthetic Rubber
Color	White
pH	10-11
Viscosity	6-9 (Cps)
Solids	17±1 (%)
Density	0.99-1.00 (g/cm <sup>3</sup> )
Shelf Life	3 years
Pot Life	1-3 months, depending on terms of storage
Packing	0.5 liter bottle 125 ml bottle
Storage	In a cold, dry place
Dilution and Cleaning	Soap and water immediately after use. After drying, Sealant Remover and rinse with water
Hands cleaning	Soap and water immediately after use. After drying, Sealant Remover and rinse with water

September 2023

Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of this product for your particular purposes prior to use. No warranties of any kind are made regarding products described or designs, data or information set forth. Adhestick Innovations Ltd. assumes no obligation or liability for the description, designs, data and information given or results obtained, all such being given and accepted at your risk.

## ADHESTICK INNOVATIONS LTD.

17 Hamelacha St., P.O.Box 11675, Afek Industrial Park, Rosh Ha'ain 4809144, Israel  
 Tel. +972 3 9027080 | Fax. +972 3 9027077 | Vat 515274389  
 info@adhestick.com