SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

BIKE7 CLEAN PH9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : BIKE7 CLEAN PH9
Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

BIKE 7*

Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

+32 14 85 97 38

info@tec7.be

*BIKE 7 is a registered trademark of Novatech International

Industrielaan 5B

Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

₲ +32 14 85 97 38

info@tec7.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

2.2. Label elements

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

2.3. Other hazards

No other hazards known

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
2-butoxyethanol	111-76-2	C<5 %	Acute Tox. 4; H332	(1)(2)(10)	Constituent
01-2119475108-36	203-905-0		Acute Tox. 4; H312		
			Acute Tox. 4; H302		
			Eye Irrit. 2; H319		
			Skin Irrit. 2; H315		

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

http://www.big.be

© BIG vzw

 $Reason \ for \ revision: \ 3.2; \ 7.2; \ 8; \ 9.1; \ 10.1; \ 11; \ 13; \ 15$

Revision number: 0200 Product number: 56129 1/15

Publication date: 2015-04-23
Date of revision: 2016-10-26

134-17438-521-en

propan-2-ol	67-63-0	C<5 %	Flam. Liq. 2; H225	(1)(2)(10)	Constituent
01-2119457558-25	200-661-7		Eye Irrit. 2; H319		
			STOT SE 3; H336		

⁽¹⁾ For H-statements in full: see heading 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Rinse with water. Take victim to a doctor if irritation persists.

After eye contact:

Rinse with water. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

No effects known.

After skin contact:

No effects known.

After eye contact:

Redness of the eye tissue.

After ingestion:

AFTER INGESTION OF HIGH QUANTITIES: Vomiting. Abdominal pain. Diarrhoea. Dizziness. Headache.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Water spray. Polyvalent foam. BC powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

No unsuitable extinguishing media known.

5.2. Special hazards arising from the substance or mixture

Upon combustion CO and CO2 are formed (carbon monoxide - carbon dioxide).

5.3. Advice for firefighters

5.3.1 Instructions:

No specific fire-fighting instructions required.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Safety glasses. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No naked flames.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Safety glasses. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Contain released product, pump into suitable containers. Plug the leak, cut off the supply.

6.3. Methods and material for containment and cleaning up

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15 Publication date: 2015-04-23
Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 2 / 15

⁽²⁾ Substance with a Community workplace exposure limit

⁽¹⁰⁾ Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Finely divided: spark- and explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Observe normal hygiene standards. Keep container tightly closed.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Store in a cool area. Keep container in a well-ventilated place. Keep out of direct sunlight. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, oxidizing agents, reducing agents, (strong) acids, (strong) bases.

7.2.3 Suitable packaging material:

No data available

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

2-Butoxyetnanoi	Time-weighted average exposure limit 8 n (indicative occupational	20 ppm
	exposure limit value)	
	Time-weighted average exposure limit 8 h (Indicative occupational	98 mg/m³
	exposure limit value)	
	Short time value (Indicative occupational exposure limit value)	50 ppm
	Short time value (Indicative occupational exposure limit value)	246 mg/m ³
		-

Time weighted average average limit 0 h /Indicative accumulational

3e	lgiu	m

- 0 -		
2-Butoxyéthanol	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	98 mg/m³
	Short time value	50 ppm
	Short time value	246 mg/m³
Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m³
	Short time value	400 ppm
	Short time value	1000 mg/m³

The Netherlands

2-Butoxyethanol	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	20 ppm	
	Time-weighted average exposure limit 8 h (Public occupational exposure 100 r limit value)		
	Short time value (Public occupational exposure limit value) 50 ppr		
	Short time value (Public occupational exposure limit value)	246 mg/m³	
2-Propanol	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	260 ppm	
	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	650 mg/m³	

France

2-Butoxyéthanol	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	10 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire 49 r contraignante)	
	Short time value (VRC: Valeur réglementaire contraignante)	50 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	246 mg/m³

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15 Publication date: 2015-04-23 Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 3 / 15

	DIRE	CLEAN PR	1 .		
Alcool isopropylique	SI	hort time value (VL: Valeu	r non réglementaire in	dicative)	400 ppm
		hort time value (VL: Valeu	r non réglementaire in	dicative)	980 mg/m³
Germany					
2-Butoxyethanol		ime-weighted average exp	oosure limit 8 h (TRGS :	900)	10 ppm
,		ime-weighted average exp		•	49 mg/m³
1		ime-weighted average exp	,		200 ppm
·		ime-weighted average exp			500 mg/m³
UK					lo-
2-Butoxyethanol		ime-weighted average exp EH40/2005))	oosure limit 8 h (Work)	lace exposure limit	25 ppm
	-	ime-weighted average exp	ocura limit 9 h /Markr	alaco ovnocuro limit	123 mg/m³
		EH40/2005))	Josule IIIIII 8 II (Work	nace exposure illilit	123 Hig/III
	<u>-</u>	hort time value (Workplac	e exposure limit (EH40)/2005))	50 ppm
		hort time value (Workplac			246 mg/m³
Propan-2-ol		ime-weighted average exp			400 ppm
·		EH40/2005))	, ,	'	
	Т	ime-weighted average exp	oosure limit 8 h (Work	olace exposure limit	999 mg/m³
	<u></u>	H40/2005))			
	_	hort time value (Workplac	<u>`</u>		500 ppm
	S	hort time value (Workplac	e exposure limit (EH40)/2005))	1250 mg/m ³
USA (TLV-ACGIH)					
2-Butoxyethanol (EGBE)	lτ	ime-weighted average exp	oosure limit 8 h (TLV - A	Adopted Value)	20 ppm
2-propanol		Time-weighted average exposure limit 8 h (TLV - Adopted Value			200 ppm
P SPS		hort time value (TLV - Ado			400 ppm
2-Butoxyethanol (Butoxyessigsäure (nac Hydrolyse))	h Urin: bei langzeitexposi vorangegangenen schic		200 mg/l	11/2012 Ständige Senatskommissio Prüfung gesundheitsschädlicher	
			100 (1	Arbeitsstoffe der DF	
2-Butoxyethanol (Butoxyessigsäure)	Urin: bei langzeitexposi		100 mg/l	11/2012 Ständige Senatskommission Prüfung gesundheitsschädlicher	
	vorangegangenen schichten			Arbeitsstoffe der DF	
Propan-2-ol (Aceton)	Urin: expositionsende,	bzw. schichtende	25 mg/l	11/2012 Ständige Senatskommissio	
	orm expositionsenae,	DEWY SOMETHING	23 1116/1	Prüfung gesundheitsschädlicher	
				Arbeitsstoffe der DF	G
Propan-2-ol (Aceton)	Vollblut: expositionsend	de, bzw. schichtende	25 mg/l	11/2012 Ständige Se	enatskommission
				Prüfung gesundheitsschädlicher	
				Arbeitsstoffe der DF	
Vitamin K-Antagonisten (Quick-Wert)	Vollblut: keine beschrär	nkung	Reduktion auf	11/2012 Ständige Se	
			nicht weniger als	Prüfung gesundheit: Arbeitsstoffe der DF	
UK			70%	Ai Deitsstoffe der DF	<u> </u>
2-Butoxyethanol (butoxyacetic acid)	Urine: post shift		240 mmol/mol		
z-Butoxyethanoi (butoxyacetic acid)	orine, post smit		creatinine		
(1		fercamine	1	
USA (BEI-ACGIH)	1		lana /	1	
2-buthoxyethanol (Butoxyacetic acid	urine: end of shift		200 mg/g		
(BAA))	1.00		creatinine	+	
2-Propanol (Acetone)	Urine: end of shift at er	ia of workweek	40 mg/L		
2 Sampling methods	d la al a				
If applicable and available it will be liste	d below.	MOCH	1402	1	
2-Butoxyethanol (Alcohols IV)	n+1	NIOSH	1403		
2-Butoxyethanol (Butyl Cellosolve solve Butoxyacetic acid	itj	OSHA NIOSH	83 8316		
,	unds)				
Butyl cellosolve (Volatile Organic compounds)		NIOSH	2549		

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

Butyl Cellosolve

Isopropanol (Volatile Organic compounds)

DNEL/DMEL - Workers

Isopropyl Alcohol (Alcohols I)

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15

Publication date: 2015-04-23

Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129

OSHA

NIOSH

NIOSH

83 2<u>5</u>49

1400

4/15

109

2-butoxyethanol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	98 mg/m³	
	Acute systemic effects inhalation	1091 mg/m³	
	Acute local effects inhalation	246 mg/m³	
	Long-term systemic effects dermal	125 mg/kg bw/day	
	Acute systemic effects dermal	89 mg/kg bw/day	

propan-2-ol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m³	
	Long-term systemic effects dermal	888 mg/kg hw/day	

DNEL/DMEL - General population

2-butoxyethanol

<u> </u>	•		
Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	59 mg/m³	
	Acute systemic effects inhalation	426 mg/m³	
	Acute local effects inhalation	147 mg/m³	
	Long-term systemic effects dermal	75 mg/kg bw/day	
	Acute systemic effects dermal	89 mg/kg bw/day	
	Long-term systemic effects oral	6.3 mg/kg bw/day	
	Acute systemic effects oral	26.7 mg/kg bw/day	

propan-2-ol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m³	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	

PNEC

2-butoxyethanol

Compartments	Value	Remark
Fresh water	8.8 mg/l	
Marine water	0.88 mg/l	
Aqua (intermittent releases)	9.1 mg/l	
STP	463 mg/l	
Fresh water sediment	34.6 mg/kg sediment dw	
Marine water sediment	3.46 mg/kg sediment dw	
Soil	2.33 mg/kg soil dw	
Oral	0.02 g/kg food	

propan-2-ol

Compartments	Value	Remark
Fresh water	140.9 mg/l	
Marine water	140.9 mg/l	
Aqua (intermittent releases)	140.9 mg/l	
STP	2251 mg/l	
Fresh water sediment	552 mg/kg sediment dw	
Marine water sediment	552 mg/kg sediment dw	
Soil	28 mg/kg soil dw	
Oral	160 mg/kg food	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Finely divided: spark- and explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work.

a) Respiratory protection:

Insufficient ventilation: wear respiratory protection. Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

Materials	Breakthrough time	Thickness	
nitrile rubber		0.35 mm	

- materials (good resistance)

Nitrile rubber.

c) Eye protection:

Safety glasses.

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15 Publication date: 2015-04-23 Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 5 / 15

d) Skin protection:

Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Liquid
Odour	Characteristic odour
Odour threshold	No data available
Colour	No data available on colour
Particle size	Not applicable (liquid)
Explosion limits	1.13 - 12.0 vol %
Flammability	Material presenting a fire hazard
Log Kow	Not applicable (mixture)
Dynamic viscosity	1 mPa.s ; 20 °C
Kinematic viscosity	1 mm ² /s ; 20 °C
Melting point	No data available
Boiling point	82 °C - 261 °C
Flash point	65 ℃
Evaporation rate	No data available
Relative vapour density	No data available
Vapour pressure	4300 hPa ; 20 °C
Solubility	water ; soluble
Relative density	1.0 ; 20 °C
Decomposition temperature	No data available
Auto-ignition temperature	230 °C
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
рН	9

9.2. Other information

Absolute density	1013 kg/m³ ; 20 °C	
------------------	--------------------	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Temperature above flashpoint: higher fire/explosion hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from naked flames/heat. Finely divided: spark- and explosionproof appliances. Finely divided: keep away from ignition sources/sparks.

10.5. Incompatible materials

Oxidizing agents, reducing agents, (strong) acids, (strong) bases.

10.6. Hazardous decomposition products

Upon combustion CO and CO2 are formed (carbon monoxide - carbon dioxide).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

BIKE7 CLEAN PH9

No (test)data on the mixture available

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15 Publication date: 2015-04-23

Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 6 / 15

2-butoxyethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	1746 mg/kg bw		Rat (male)	Experimental value	
Oral	LD50	Equivalent to OECD 401	1300 mg/kg bw		Rat (male/female)	Experimental value	
Oral	LD50	OECD 401	1414 mg/kg bw		Guinea pig (male/female)	Experimental value	
Dermal			category 4			Annex VI	
Dermal	LD50	OECD 402	> 2000 mg/kg bw		Rat (male/female)	Experimental value	
Inhalation			category 4			Expert judgement	
Inhalation (vapours)	LC50	Equivalent to OECD 403	450 ppm	4 h	Rat (female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	486 ppm	4 h	Rat (male)	Experimental value	
Inhalation (vapours)	LC50	OECD 403	> 800 ppm	4 h	Rat (female)	Experimental value	

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	13120 mg/kg bw	24 h	Rabbit	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	6 h	Rat (male/female)	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified for acute toxicity

Corrosion/irritation

BIKE7 CLEAN PH9

No (test)data on the mixture available

$\underline{\text{2-butoxyethanol}}$

esult	Method	Exposure time	Time point	Species	Value	Remark
					determination	
ritating	OECD 405	24 h	24; 48; 72 hours	Rabbit	'	٠ .
						with rinsing
ritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	
ri	tating	tating OECD 405	tating OECD 405 24 h	tating OECD 405 24 h 24; 48; 72 hours	tating OECD 405 24 h 24; 48; 72 hours Rabbit	determination tating OECD 405 24 h 24; 48; 72 hours Rabbit Experimental value

propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye	0	Equivalent to OECD 405		24 hours	Rabbit	Experimental value	Single treatment
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

BIKE7 CLEAN PH9

No (test)data on the mixture available

2-butoxyethanol

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406	,	Guinea pig (male/female)	Experimental value	

propan-2-ol

Rou	ute of exposure	Result	Method		Observation time point	Species	Value determination	Remark
Skii	n	Not sensitizing		3 weeks (6h/day, 1 day/week)	l '	Guinea pig (male/female)	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified as sensitizing for skin Not classified as sensitizing for inhalation

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15

Publication date: 2015-04-23

Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 7 / 15

Specific target organ toxicity

BIKE7 CLEAN PH9

No (test)data on the mixture available

2-butoxyethanol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
								determination
Oral (drinking	NOAEL	Equivalent to	< 69 mg/kg			90 days (continuous)	Rat (male)	Experimental
water)		OECD 408	bw/day					value
Dermal	NOAEL	Equivalent to	150 mg/kg		No effect	90 day(s)	Rabbit	Experimental
		OECD 411	bw/day				(male/female)	value
Inhalation	LOAEC	OECD 453	152 mg/m ³	Blood	Histology	102 weeks (daily, 5	Rat	Experimental
						days/week)	(male/female)	value

propan-2-ol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm			104 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value
Inhalation (vapours)	NOAEL	OECD 413	5000 ppm			13 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value
Inhalation (vapours)	Dose level	OECD 403		Central nervous system	Drowsiness, dizziness	6 h	Rat (male/female)	Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

BIKE7 CLEAN PH9

No (test)data on the mixture available

<u>2-butoxyethanol</u>

	Result	Method	Test substrate	Effect	Value determination
	Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value
	Negative	Equivalent to OECD 476	Hamster ovary		Experimental value
pro	pan-2-ol				

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
activation, negative without				
metabolic activation				
Negative with metabolic	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value
activation, negative without				
metabolic activation				

Mutagenicity (in vivo)

BIKE7 CLEAN PH9

No (test)data on the mixture available

2-butoxyethanol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD		Mouse (male)		Experimental value
	474				

propan-2-ol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD		Mouse (male/female)		Experimental value
	474				

 $\label{lem:continuous} \mbox{ Judgement is based on the relevant ingredients }$

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

BIKE7 CLEAN PH9

No (test)data on the mixture available

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15

Publication date: 2015-04-23

Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 8 / 15

2-butoxyethanol

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
exposure								determination
Inhalation	NOAEC	Equivalent to	0 ppm	2 year(s)	Rat	Neoplastic		Experimental
		OECD 451			(male/female)	effects		value
Inhalation	NOAEC	Equivalent to	125 ppm	2 year(s)	Mouse	Neoplastic		Experimental
		OECD 451			(male/female)	effects		value

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	- 0-	Value determination
Inhalation	NOEL	Equivalent to	5000 ppm	104 weeks (6h/day,	Mouse	No carcinogenic		Experimental
(vapours)		OECD 451		5 days/week)	(male/female)	effect		value

Judgement is based on the relevant ingredients

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

BIKE7 CLEAN PH9

No (test)data on the mixture available

2-butoxyethanol

	Parameter	Method	Value	Exposure time	Species	Effect	- 0-	Value determination
Developmental toxicity	NOAEL		100 mg/kg bw/day	5 day(s)	Rat	Weight changes		Experimental value
	NOAEC	Equivalent to OECD 414	100 ppm	12 day(s)	Rabbit			Experimental value
Effects on fertility	NOAEL (P/F1/F2)	Other	720 mg/kg bw/day		Mouse (male/female)	No effect		Experimental value

propan-2-ol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Experimental value
	NOAEL	Equivalent to OECD 414	480 mg/kg bw/day	13 day(s)	Rabbit	No effect	Foetus	Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat (female)	No effect		Experimental value
Effects on fertility	NOAEL	Equivalent to OECD 415	853 mg/kg bw/day	21 day(s) - 70 day(s)	Rat (male/female)	No effect		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

BIKE7 CLEAN PH9

No (test)data on the mixture available

Chronic effects from short and long-term exposure

BIKE7 CLEAN PH9

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

BIKE7 CLEAN PH9

No (test)data on the mixture available

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15 Publication date: 2015-04-23

Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 9 / 15

2-butoxyethanol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	1474 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	1550 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	EC50	OECD 201	911 mg/l	72 h	Pseudokirchnerie Ila subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	88 mg/l	72 h	Pseudokirchnerie Ila subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity fish	NOEC	Equivalent to OECD 204	> 100 mg/l	21 day(s)	Danio rerio	Semi-static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity aquatic crustacea	NOEC	OECD 211	100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro- organisms	Toxicity threshold	Equivalent to DIN 38412/8	700 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Nominal concentration

propan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt	Value determination
							water	
Acute toxicity fishes	LC50	OECD 203	9640 mg/l	96 h	· .	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea		Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system		Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	EC0		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Toxicity aquatic micro- organisms	EC50	ISO 8192	41676 mg/l	30 minutes	Bacteria			Experimental value; Activated sludge

Judgement is based on the relevant ingredients

Conclusion

pH shift

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

2-butoxyethanol

Biodegradation water

	Method	Value	Duration	Value determination						
	OECD 301B: CO2 Evolution Test	90.4 %	28 day(s)	Experimental value						
_	Phototypusformation air (DTEG air)									

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.90	5.46 h	1500000 /cm³	Calculated value
	-	-	

propan-2-ol

Biodegradation water

Method	Value	Duration	Value determination
OECD 301E: Modified OECD Screening Test	95 %	21 day(s)	Experimental value

Conclusion

The surfactant(s) is/are biodegradable

12.3. Bioaccumulative potential

BIKE7 CLEAN PH9

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

2-butoxyethanol

Log Kow

Method	Remark	Value	Temperature	Value determination
		0.81	20 °C	Test data

propan-2-ol

Log Kow

Method	Remark	Value	Temperature	Value determination
Other			25 °C	Weight of evidence approach

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15

Publication date: 2015-04-23

Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 10 / 15

Conclusion

Does not contain bioaccumulative component(s)

12.4. Mobility in soil

2-butoxyethanol

Volatility (Henry's Law constant H)

Value	Method	Temperature	Remark	Value determination
0.041 atm m³/mol	Other	20 °C		Experimental value

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level I	0.31 %	0 %	0.01 %	0.59 %	99.09 %	QSAR
Mackay level III	1.01 %	0 %	0.37 %	51.9 %	46.8 %	QSAR

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

BIKE7 CLEAN PH9

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

2-butoxyethanol

Ground water

Ground water pollutant

propan-2-ol

Ground water

Ground water pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Can be considered as non hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 30 (separately collected fractions (except 15 01): detergents other than those mentioned in 20 01 29). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Neutralize. Remove to an authorized incinerator with energy recovery. Remove waste in accordance with local and/or national regulations. Avoid discharge of large amounts into the sewer.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 02 (plastic packaging).

SECTION 14: Transport information

Environmentally hazardous substance mark

Road (ADR)

14.1. UN number		
Transport	Not subject	
14.2. UN proper shipping name		
14.3. Transport hazard class(es)		
Hazard identification number		
Class		
Classification code		
14.4. Packing group		
Packing group		
Labels		
14.5. Environmental hazards		

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15 Publication date: 2015-04-23 Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 11 / 15

no

14	6. Special precautions for user	
1	Special previsions	
	Limited quantities	
Rail (I	RID)	
	1. UN number	
		Not subject
	2. UN proper shipping name	
	3. Transport hazard class(es)	
	Hazard identification number	
	Class	
	Classification code	
	4. Packing group	
	Packing group	
,	Labels	
1	5. Environmental hazards Environmentally hazardous substance mark	no.
	6. Special precautions for user	no
	Special prevaitions	
	Limited quantities	
	·	
Inland	d waterways (ADN)	
14.	1. UN number	
	Transport	Not subject
	2. UN proper shipping name	
	3. Transport hazard class(es)	
	Class	
	Classification code	
	4. Packing group	
	Packing group	
	Labels	
	5. Environmental hazards	
	,	no
	6. Special precautions for user	
	Special provisions	
	Limited quantities	
Sea (I	MDG/IMSBC)	
	1. UN number	
		Not subject
	2. UN proper shipping name	,
	3. Transport hazard class(es)	
	Class	
	4. Packing group	
	Packing group	
	Labels	
14.	5. Environmental hazards	
1	Marine pollutant	
		no
14.	6. Special precautions for user	
	Special provisions	
	Limited quantities	
14.	7. Transport in bulk according to Annex II of Marpol and the IBC Code	
	Annex II of MARPOL 73/78	
Air (10	CAO-TI/IATA-DGR)	
1	1. UN number	Not subject
	·	Not subject
	2. UN proper shipping name	
	3. Transport hazard class(es)	
	Class	
	4. Packing group	
	Packing group	
	Labels E. Divisormental bazards	
	5. Environmental hazards	no
	,	no
	6. Special precautions for user	
	Special provisions	
	limited quantities: maximum net quantity per packaging	

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15

Publication date: 2015-04-23

Date of revision: 2016-10-26

 Revision number: 0200
 Product number: 56129
 12 / 15

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
3.20 %	
32.367 g/l	

Indicative occupational exposure limit values (Directive 98/24/EC, 2000/39/EC and 2009/161/EU)

Product name	Skin resorption
2-Butoxyethanol	Skin

Ingredients according to Regulation (EC) No 648/2004 and amendments

<5% phosphates, <5% non-ionic surfactants, perfumes, limonene, cinnamal

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

and use of certain da	angerous substances, mixtures and articles.	
	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· 2-butoxyethanol · propan-2-ol	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304,4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage"; b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Ar
· propan-2-ol	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only".3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC.4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

National legislation Belgium

BIKE7 CLEAN PH9

No data available

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15 Publication date: 2015-04-23 Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 13 / 15

2-butoxyethanol

Résorption peau	2-Butoxyéthanol; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue	
	une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de	
	l'agent dans l'air.	

National legislation The Netherlands

BIKE7 CLEAN PH9

Waterbezwaarlijkheid	B (5)		
butoxyethanol			
Huidopname (wettelijk)	2-Butoxyethanol; H		

National legislation France

BIKE7 CLEAN PH9

No data available

2-butoxyethanol

_		
	VME - Risque de pénétration	2-Butoxyéthanol; PP
	percutanée	

National legislation Germany

BIKE7 CLEAN PH9

WGK	1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender	
	Stoffe (VwVwS) of 27 July 2005 (Anhang 4)	
2-butoxyethanol		
TA-Luft	5.2.5	
TRGS900 - Risiko der	2-Butoxyethanol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen	
Fruchtschädigung	Grenzwertes nicht befürchtet zu werden	
Hautresorptive Stoffe	2-Butoxyethanol; H; Hautresorptiv	
propan-2-ol		
TA-Luft	5.2.5	
TRGS900 - Risiko der	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen	
Fruchtschädigung	Grenzwertes nicht befürchtet zu werden	

National legislation United Kingdom

BIKE7 CLEAN PH9

No data available

2-butoxyethanol

=			
	Skin absorption	2-Butoxyethanol; Sk	

Other relevant data

BIKE7 CLEAN PH9

No data available

2-butoxyethanol

	IARC - classification	3; 2-butoxyethanol	
	TLV - Carcinogen	2-Butoxyethanol (EGBE); A3	
pi	propan-2-ol		
	TLV - Carcinogen	2-propanol; A4	
	IARC - classification	3; Isopropanol	

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

(*) INTERNAL CLASSIFICATION BY BIG

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 % LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15 Publication date: 2015-04-23
Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 14 / 15

OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration
STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3.2; 7.2; 8; 9.1; 10.1; 11; 13; 15 Publication date: 2015-04-23
Date of revision: 2016-10-26

Revision number: 0200 Product number: 56129 15 / 15