

## Trigger Shifters

Model No.	DLMZ30	DLMZ3N	DLMZ3I
	RW	RW	RW
Side and Speed	Right 12-Spd	Right 12-Spd	Right 12-Spd
Gear Display	Podium Top	X	X
SHIMANO® I-SPEC® II Compatible*	X	X	●
Dual Release Function	●	●	●
Cable Adjuster	●	●	●
Multiple Shifts (Max.)	4	4	4
Clamp Screw	Stainless Steel	Stainless Steel	Stainless Steel
Large Lever	Aluminum	Aluminum	Aluminum
Small Lever	Engineering Polymers	Engineering Polymers	Engineering Polymers
Cable Type	Slick-Stainless	Slick-Stainless	Slick-Stainless
Cable Length	2,100mm	2,100mm	2,100mm
Casing Compatibility	SP	SP	SP
Finish	Black	Black	Black
Average Weight	139g	125g	123g

\* SHIMANO® and I-SPEC® are registered trademarks of Shimano, Inc.

Model No.	DLMX30		DLMX3N		DLMX3I	
	RE	LL	RE	LL	RE	LL
Side and Speed	Right 11-Spd	Left 2/3-Spd	Right 11-Spd	Left 2/3-Spd	Right 11-Spd	Left 2/3-Spd
Gear Display	Podium Top		X		X	
SHIMANO® I-SPEC® II Compatible*	X		X		●	
Dual Release Function	●		●		●	
Cable Adjuster	●		●		●	
2/3 Mode Converter	X	●	X	●	X	●
Multiple Shifts (Max.)	4	1	4	1	4	1
Clamp Screw	Stainless Steel		Stainless Steel		Stainless Steel	
Large Lever	Aluminum		Aluminum		Aluminum	
Small Lever	Engineering Polymers		Engineering Polymers		Engineering Polymers	
Cable Type	Slick-Stainless		Slick-Stainless		Slick-Stainless	
Cable Length	2,100mm	1,700mm	2,100mm	1,700mm	2,100mm	1,700mm
Casing Compatibility	SP		SP		SP	
Finish	Black		Black		Black	
Average Weight	139g	140g	125g	126g	123g	124g

\* SHIMANO® and I-SPEC® are registered trademarks of Shimano, Inc.

## Trigger Shifters

Model No.	DLMS30		DLMS3N		DLMS3I		DLMS10	
	RT	LL	RT	LL	RT	LL	RT	LL
Side and Speed	Right 10-Spd	Left 2/3-Spd	Right 10-Spd	Left 2/3-Spd	Right 10-Spd	Left 2/3-Spd	Right 10-Spd	Left 2/3-Spd
Gear Display	Podium Top		X		X		Podium Top	
SHIMANO® I-SPEC® II Compatible*	X		X		●		X	
Dual Release Function	●		●		●		●	
Cable Adjuster	●		●		●		●	
2/3 Mode Converter	X	●	X	●	X	●	X	●
Multiple Shifts (Max.)	4	1	4	1	4	1	4	1
Clamp Screw	Stainless Steel		Stainless Steel		Stainless Steel		SCM435 Chromoly	
Large Lever	Aluminum		Aluminum		Aluminum		Engineering Polymers	
Small Lever	Engineering Polymers		Engineering Polymers		Engineering Polymers		Engineering Polymers	
Cable Type	Slick-Stainless		Slick-Stainless		Slick-Stainless		Slick-Galvanized	
Cable Length	2,100mm	1,700mm	2,100mm	1,700mm	2,100mm	1,700mm	2,100mm	1,700mm
Casing Compatibility	SP		SP		SP		SP	
Finish	Black		Black		Black		Black	
Average Weight	139g	140g	125g	126g	123g	124g	143g	144g

\* SHIMANO® and I-SPEC® are registered trademarks of Shimano, Inc.

Model No.	DLM930		DLM900		DLM500		DLM400		
	R9	LL	R9	LL	R8	L3	R8	R7	L3
Side and Speed	Right 9-Spd	Left 2/3-Spd	Right 9-Spd	Left 2/3-Spd	Right 8-Spd	Left 3-Spd	Right 8-Spd	Right 7-Spd	Left 3-Spd
Gear Display	Podium Top		Podium Top		Podium Top		Podium Top		
SHIMANO® I-SPEC® II Compatible*	X		X		X		X		
Dual Release Function	●		●		●		●		
Cable Adjuster	●		●		●		●		
2/3 Mode Converter	X	●	X	●	X		X		
Multiple Shifts (Max.)	6	1	6	1	5	1	5	5	1
Clamp Screw	Stainless Steel		SCM435 Chromoly		SCM435 Chromoly		SCM435 Chromoly		
Large Lever	Aluminum		Engineering Polymers		Aluminum		Engineering Polymers		
Small Lever	Engineering Polymers		Engineering Polymers		Engineering Polymers		Engineering Polymers		
Cable Type	Slick-Stainless		Slick-Galvanized		Slick-Galvanized		Slick-Galvanized		
Cable Length	2,100mm	1,700mm	2,100mm	1,700mm	2,100mm	1,700mm	2,100mm	2,100mm	1,700mm
Casing Compatibility	SP		SP		SP		SP	2SP & ↑	2SP & ↑
Finish	Black		Black		Black		Black		
Average Weight	139g	140g	143g	144g	140g	141g	143g	143g	144g

\* SHIMANO® and I-SPEC® are registered trademarks of Shimano, Inc.

## Trigger Shifters

Model No.	DLM90		DLM33			
	R9	L3	R8	R7	R6	L3
Side and Speed	Right 9-Spd	Left 3-Spd	Right 8-Spd	Right 7-Spd	Right 6-Spd	Left 3-Spd
Gear Display	Podium Top		Podium Top			
SHIMANO® I-SPEC® II Compatible*	X		X			
Dual Release Function	X		X			
Cable Adjuster	●		●			
2/3 Mode Converter	X		X			
Multiple Shifts (Max.)	6	1	6	5	4	1
Clamp Screw	SUS302 Stainless Steel		SCM435 Chromoly			
Large Lever	Engineering Polymers		Engineering Polymers			
Small Lever	Engineering Polymers		Engineering Polymers			
Cable Type	Slick-Galvanized		Galvanized			
Cable Length	2,050mm	1,600mm	2,050mm			1,600mm
Casing Compatibility	SP		SP	2SP & ↑	2SP & ↑	2SP & ↑
Finish	Black		Black			
Average Weight	158g	157g	158g	158g	158g	157g

\* SHIMANO® and I-SPEC® are registered trademarks of Shimano, Inc.