SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

CHAIN CLEAN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

: CHAIN CLEAN Product name

Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

1.2.2 Uses advised against

No uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

BIKE 7*

Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

4 +32 14 85 97 38

info@tec7.be

*BIKE 7 is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

4 +32 14 85 97 38

info@tec7.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :

+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (FC) No 1272/2008

Class	Category	Hazard statements
Asp. Tox.	category 1	H304: May be fatal if swallowed and enters airways.
Eye Irrit.	category 2	H319: Causes serious eye irritation.

2.2. Label elements





Contains: hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics.

Signal word

H-statements

May be fatal if swallowed and enters airways. H304

Causes serious eye irritation. H319

P-statements

P101 If medical advice is needed, have product container or label at hand.

Keep out of reach of children. P102

P280 Wear eye protection

Wash hands thoroughly after handling. P264

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P331 Do NOT induce vomiting.

IF SWALLOWED: Immediately call a POISON CENTER/doctor. P301 + P310

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be

© BIG vzw

Reason for revision: 3.2 Revision number: 0001

Publication date: 2019-01-08 Date of revision: 2019-12-18

Product number: 61330

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No other hazards known

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119456620-43		C>30%	Asp. Tox. 1; H304	(1)(10)	Constituent
2-butoxyethanol 01-2119475108-36	111-76-2 203-905-0	C<5%	Acute Tox. 4; H332 Acute Tox. 4; H312 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319	(1)(2)(10)	Constituent
(Z)-Octadec-9-enylamine, ethoxylated	26635-93-8 500-048-7	C<5%	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Irrit. 2; H315 Aquatic Acute 1; H400	(1)	Constituent

⁽¹⁾ For H-statements in full: see heading 16

- (2) Substance with a Community workplace exposure limit
- (10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Alcohol consumption increases the toxicity.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Soap may be used. Do not apply (chemical) neutralizing agents without medical advice. Take victim to a doctor if irritation persists.

After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply (chemical) neutralizing agents without medical advice. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Do not induce vomiting. Do not apply (chemical) neutralizing agents without medical advice. Consult a doctor/medical service if you feel unwell

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

No effects known.

After skin contact:

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

After eye contact:

Irritation of the eye tissue. Redness of the eye tissue.

After ingestion:

Risk of aspiration pneumonia. Vomiting. Headache. Abdominal pain. Diarrhoea. Drowsiness.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

Reason for revision: 3.2 Publication date: 2019-01-08

Date of revision: 2019-12-18

 Revision number: 0001
 Product number: 61330
 2 / 14

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher. Major fire: Class B foam (not alcohol-resistant).

5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.

Major fire: Water; risk of puddle expansion.

5.2. Special hazards arising from the substance or mixture

Upon combustion: formation of CO, CO2 and small quantities of nitrous vapours.

5.3. Advice for firefighters

5.3.1 Instructions:

No specific fire-fighting instructions required.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Safety glasses (EN166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: compressed air apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No naked flames.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Safety glasses (EN166). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Contain released product.

6.3. Methods and material for containment and cleaning up

Solid spill: take up in absorbent material. Scoop absorbed substance into closing containers. Clean contaminated surfaces with a soap solution. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Avoid prolonged and repeated contact with skin. Remove contaminated clothing immediately. Keep container tightly closed.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Protect against frost. Ventilation at floor level. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, reducing agents, oxidizing agents, (strong) acids, (strong) bases.

7.2.3 Suitable packaging material:

No data available

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

2-Butoxyethanol	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	ppm
	Time-weighted average exposure limit 8 h (Indicative occupational 98	mg/m³
	exposure limit value)	
	Short time value (Indicative occupational exposure limit value) 50	ppm

Reason for revision: 3.2 Publication date: 2019-01-08
Date of revision: 2019-12-18

Revision number: 0001 Product number: 61330 3 / 14

2-Butoxyethanol		Short time value (Indicativ	e occupational exposure	limit value)	246 mg/m ³
Belgium					
2-Butoxyéthanol	-	Time-weighted average ex	vnosure limit 8 h		20 ppm
· ·		Time-weighted average exposure limit 8 h			98 mg/m³
	t t	Short time value	tposare mine o n		50 ppm
		Short time value			246 mg/m³
	l	Short time value			2-10 1116/111
The Netherlands	į.	rian a consistent al accessor as			lao
2-Butoxyethanol	<u> </u>	Time-weighted average ex limit value)			
		Time-weighted average ex limit value)	posure limit 8 h (Public	occupational exposure	100 mg/m³
		Short time value (Public o	ccupational exposure lim	it value)	50 ppm
		Short time value (Public o	ccupational exposure lim	it value)	246 mg/m ³
France					
2-Butoxyéthanol		Time-weighted average excontraignante)	xposure limit 8 h (VRC: V	aleur réglementaire	10 ppm
		Time-weighted average excontraignante)	xposure limit 8 h (VRC: V	aleur réglementaire	49 mg/m³
		Short time value (VRC: Va	leur réglementaire contr	aignante)	50 ppm
		Short time value (VRC: Va		<u> </u>	246 mg/m³
_	1			. 6 ,	<u>, , , , , , , , , , , , , , , , , , , </u>
Germany		Time waighted average a	magura limit 0 h /TDCC 0	00)	10
		Time-weighted average ex Time-weighted average ex			10 ppm 49 mg/m³
		rime-weighted average ex	(posure liffiit 8 fi (1RGS 9	00)	49 mg/m ⁻
UK					T
(<u>(</u> T (<u>(</u>		ime-weighted average exposure limit 8 h (Workplace exposure limit EH40/2005))			25 ppm
		Time-weighted average ex (EH40/2005))	kposure limit 8 h (Workp	ace exposure limit	123 mg/m³
		Short time value (Workpla	ice exposure limit (EH40,	/2005))	50 ppm
Į s		Short time value (Workpla	ice exposure limit (EH40,	/2005))	246 mg/m ³
USA (TLV-ACGIH)					
2-Butoxyethanol (EGBE)	-	Time-weighted average ex	posure limit 8 h (TLV - A	dopted Value)	20 ppm
b) National biological limit valuesIf limit values are applicable and availab	le these will be listed bel	ow.			
Germany	1		1 /	1	
2-Butoxyethanol (Butoxyessigsäure	Urin: expositionsende		150 mg/g	11/2016 Ständige Se	
(nach Hydrolyse))	bei langzeitexposition vorangegangenen sch		Kreatinin	Prüfung gesundheits Arbeitsstoffe der DFG	
2-Butoxyethanol (Butoxyessigsäure	Urin: expositionsende		150 mg/g	11/2016 Ständige Se	
(nach Hydrolyse))	bei langzeitexposition			Prüfung gesundheits	
<u> </u>	vorangegangenen sch	icnten		Arbeitsstoffe der DF0	J
2. Dutanusthanal (hutanusaatia asid)	Heiman mach -leift		240 mm = 1/1	1	
2-Butoxyethanol (butoxyacetic acid)	Urine: post shift		240 mmol/mol creatinine		
USA (BEI-ACGIH)	_				
2-buthoxyethanol (Butoxyacetic acid (BAA))	urine: end of shift		200 mg/g creatinine		
2 Sampling methods					<u> </u>
Product name		Test	Number		
2-Butoxyethanol (Alcohols IV)		NIOSH	1403		
2-Butoxyethanol (Butyl Cellosolve solve	nt)	OSHA	83		
Butoxyacetic acid		NIOSH	8316		
Butyl cellosolve (Volatile Organic compo	ounds)	NIOSH	2549		
Butyl Cellosolve		OSHA	83		
Kerosene (Naphthas)		NIOSH	1550		

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

Reason for revision: 3.2 Publication date: 2019-01-08

Date of revision: 2019-12-18

Revision number: 0001 Product number: 61330 4 / 14

2-butoxyethanol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	98 mg/m³	
	Acute systemic effects inhalation	1091 mg/m³	
	Acute local effects inhalation	246 mg/m ³	
	Long-term systemic effects dermal	125 mg/kg bw/day	
	Acute systemic effects dermal	89 mg/kg bw/day	

<u>DNEL/DMEL - General population</u> 2-butoxyethanol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	59 mg/m³	
	Acute systemic effects inhalation	426 mg/m³	
	Acute local effects inhalation	147 mg/m³	
	Long-term systemic effects dermal	75 mg/kg bw/day	
	Acute systemic effects dermal	89 mg/kg bw/day	
	Long-term systemic effects oral	6.3 mg/kg bw/day	
	Acute systemic effects oral	26.7 mg/kg bw/day	

PNEC

2-butoxyethanol

Compartments	Value	Remark
Fresh water	8.8 mg/l	
Marine water	0.88 mg/l	
Fresh water (intermittent releases)	26.4 mg/l	
STP	463 mg/l	
Fresh water sediment	34.6 mg/kg sediment dw	
Marine water sediment	3.46 mg/kg sediment dw	
Soil	2.33 mg/kg soil dw	
Oral	20 mg/kg food	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Avoid prolonged and repeated contact with skin. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Remark	Protection index
nitrile rubber	> 480 minutes	0.35 mm	Class 6

c) Eye protection:

Face shield (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Liquid
Odour	Characteristic odour
Odour threshold	No data available
Colour	No data available on colour
Particle size	Not applicable (liquid)
Explosion limits	0.6 - 10.6 vol %
Flammability	Non-flammable
Log Kow	Not applicable (mixture)
Dynamic viscosity	1 mPa.s ; 20 °C
Kinematic viscosity	1 mm²/s ; 40 °C
Melting point	No data available
Boiling point	173 °C - 240 °C
Evaporation rate	0.08 ; Butyl acetate
Relative vapour density	No data available
Vapour pressure	8 hPa ; 20 °C

Reason for revision: 3.2 Publication date: 2019-01-08 Date of revision: 2019-12-18

Revision number: 0001 Product number: 61330 5/14

Solubility	Water ; insoluble
Relative density	0.79 ; 20 °C
Decomposition temperature	No data available
Auto-ignition temperature	230 °C
Flash point	73 °C
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
рН	No data available

9.2. Other information

Absolute density 790 kg/m³; 20 °C	
-----------------------------------	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Temperature above flashpoint: higher fire/explosion hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Keep away from naked flames/heat.

10.5. Incompatible materials

Reducing agents, oxidizing agents, (strong) acids, (strong) bases.

10.6. Hazardous decomposition products

Upon combustion: formation of CO, CO2 and small quantities of nitrous vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

CHAIN CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5.6 mg/l	4 h	Rat (male / female)	Experimental value	

2-butoxyethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	1746 mg/kg bw		Rat (male)	Experimental value	
Dermal			category 4			Annex VI	
Dermal	LD50	OECD 402	> 2000 mg/kg bw		Rat (male / female)	Experimental value	
Inhalation			category 4			Expert judgement	
Inhalation (vapours)	LC50	Equivalent to OECD 403	450 ppm	4 h	Rat (female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	486 ppm	4 h	Rat (male)	Experimental value	

(Z)-Octadec-9-enylamine, ethoxylated

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral			category 4			Literature study	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

Reason for revision: 3.2 Publication date: 2019-01-08

Date of revision: 2019-12-18

Revision number: 0001 Product number: 61330 6 / 14

CHAIN CLEAN

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Not irritating	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

2-butoxyethanol

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Irritating	OECD 405	24 h	24; 48; 72 hours	Rabbit	'	Single treatment with rinsing
Skin	Irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

(Z)-Octadec-9-enylamine, ethoxylated

Route of exposure	Result	Method	Exposure time	Time point	- •	Value determination	Remark
Eye	Serious eye damage; category 1					Literature study	
Skin	Irritating; category 2					Literature study	

Conclusion

Causes serious eye irritation.

Not classified as irritating to the skin

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

CHAIN CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		Guinea pig (female)	Experimental value	

2-butoxyethanol

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406	24; 48 hours	Guinea pig (male / female)	Experimental value	

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

CHAIN CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients hydrocarbons. C11-C14 n-alkanes isoalkanes cyclics < 2% aromatics

Route of exposure	Parameter	1			Effect	Exposure time	Species	Value
Route of exposure	rarameter	ivietilou	value	Oigaii	Ellect	Exposure time		determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 422	≥ 1000 mg/kg bw/day		No effect	003 week(s)		Experimental value
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	> 10400 mg/m³ air			13 weeks (6h / day, 5 days / week)	` '	Experimental value

2-butoxyethanol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	 Value determination
Oral (drinking water)	NOAEL	Equivalent to OECD 408	< 69 mg/kg bw/day			90 days (continuous)	 Experimental value
Dermal	NOAEL	Equivalent to OECD 411	150 mg/kg bw/day		No effect	90 day(s)	 Experimental value
Inhalation	LOAEC	OECD 453	152 mg/m ³	Blood		102 weeks (daily, 5 days / week)	 Experimental value

Reason for revision: 3.2 Publication date: 2019-01-08 Date of revision: 2019-12-18

Revision number: 0001 Product number: 61330 7 / 14

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

CHAIN CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

<u>hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics</u>

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	

2-butoxyethanol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	
Negative	Equivalent to OECD 476	Hamster ovary		Experimental value	

Mutagenicity (in vivo)

CHAIN CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (stomach tube))	Equivalent to OECD		Mouse (male / female)	Bone marrow	Experimental value
	474				

2-butoxyethanol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD		Mouse (male)		Experimental value
	474				

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

CHAIN CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

<u>hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics</u>

	Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
	exposure								determination
	Inhalation	NOAEC	Equivalent to	> 2200 mg/m ³	105 weeks (6h / day,	Rat (female)	No carcinogenic		Experimental
	(vapours)		OECD 453	air	5 days / week)		effect		value
-h	utoxvethanol		-	-	-	-	-		

<u>2-butoxyethanol</u>

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
exposure								determination
Inhalation	NOAEC	Equivalent to OECD 451	0 ppm	2 year(s)	Rat (male / female)	Neoplastic effects		Experimental value
Inhalation	NOAEC	Equivalent to OECD 451	125 ppm	2 year(s)	Mouse (male / female)	Neoplastic effects		Experimental value

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

CHAIN CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 3.2 Publication date: 2019-01-08
Date of revision: 2019-12-18

Revision number: 0001 Product number: 61330 8 / 14

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	≥ 5220 mg/m³ air	10 days (6h / day)	Rat	No effect		Experimental value
Maternal toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	≥ 5220 mg/m³	10 days (6h / day)	Rat	No effect		Experimental value
Effects on fertility (Oral (stomach tube))	NOAEL	Equivalent to OECD 415	≥ 3000 mg/kg bw/day	13 weeks (7 days / week)	Rat (male)	No effect		Experimental value

2-butoxyethanol

	Parameter	Method	Value	Exposure time	Species	Effect	0	Value determination
Developmental toxicity	NOAEL	OECD 414	100 mg/kg bw/day	5 day(s)	Rat	Weight changes		Experimental value
	NOAEC	Equivalent to OECD 414	100 ppm	12 day(s)	Rabbit			Experimental value
Effects on fertility	NOAEL (P/F1/F2)		720 mg/kg bw/day	14 weeks (daily)	Mouse (male / female)	No effect	l	Experimental value

Conclusion

Not classified for reprotoxic or developmental toxicity

Aspiration hazard

Classification of the mixture is based on test data on the mixture as a whole May be fatal if swallowed and enters airways.

Toxicity other effects

CHAIN CLEAN

No (test)data on the mixture available

Classification is based on the relevant ingredients hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Parameter	Method	Value	Organ	Effect	Exposure time	Value determination
			Skin	Skin dryness or cracking		Literature study Skin

Conclusion

Repeated exposure may cause skin dryness or cracking.

Chronic effects from short and long-term exposure

CHAIN CLEAN

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

CHAIN CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 1000 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	> 1000 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EL50	OECD 201	> 1000 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; GLP
	NOELR	OECD 201	1000 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system		Experimental value; GLP
Long-term toxicity fish	NOELR		0.173 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Growth rate
Long-term toxicity aquatic crustacea	NOELR		1.22 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR; Reproduction

Reason for revision: 3.2 Publication date: 2019-01-08

Date of revision: 2019-12-18

Revision number: 0001 Product number: 61330 9/14

2-butoxyethanol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	1474 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	1550 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	EC50	OECD 201	911 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	88 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity fish	NOEC	Equivalent to OECD 204	> 100 mg/l	21 day(s)	Danio rerio	Semi-static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity aquatic crustacea	NOEC	OECD 211	100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro- organisms	Toxicity threshold	Equivalent to DIN 38412/8	700 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Nominal concentration

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation water

Method	Value	Duration	Value determination	
OECD 301F: Manometric Respirometry Test	80 %; GLP	28 day(s)	Experimental value	

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination	
AOPWIN v1.92	9.210 h	1500000 /cm³	Calculated value	

2-butoxyethanol

В	Biodegradation water									
	Method	Value	Duration	Value determination						
	OECD 301B: CO2 Evolution Test	90.4 %	28 dav(s)	Experimental value						

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.90	5.46 h	1500000 /cm³	Calculated value

Conclusion

The surfactant(s) is/are biodegradable according to Regulation (EC) No 648/2004

12.3. Bioaccumulative potential

CHAIN CLEAN

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		207.7 l/kg; Fresh weight			Estimated value

Log Kow

Method	Remark	Value	Temperature	Value determination
KOWWIN		6.23		Estimated value

2-butoxyethanol

Log Kow

Method	Remark	Value	Temperature	Value determination
		0.81	20 °C	Test data

(Z)-Octadec-9-enylamine, ethoxylated

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

Reason for revision: 3.2 Publication date: 2019-01-08
Date of revision: 2019-12-18

 Revision number: 0001
 Product number: 61330
 10 / 14

No straightforward conclusion can be drawn based upon the available numerical values

12.4. Mobility in soil

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Percent distribution

Method	Fraction air	 Fraction sediment	Fraction soil	Fraction water	Value determination
Fugacity Model Level III	22.4 %	6.15 %	2.51 %	69 %	Calculated value

2-butoxyethanol

Volatility (Henry's Law constant H)

Value	Method	Temperature	Remark	Value determination
0.041 atm m³/mol		20 °C		Experimental value

Percent distribution

Method	Fraction air		Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level I	0.31 %	0 %	0.01 %	0.59 %	99.09 %	QSAR
Mackay level III	1.01 %	0 %	0.37 %	51.9 %	46.8 %	QSAR

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

CHAIN CLEAN

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Groundwater

Groundwater pollutant

2-butoxyethanol

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 29* (separately collected fractions (except 15 01): detergents containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber with energy recovery. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR), Rail (RID), Inland waterways (ADN), Sea (IMDG/IMSBC), Air (ICAO-TI/IATA-DGR)

14.1. ON number	
Transport	Not subject
14.2. UN proper shipping name	
14.3. Transport hazard class(es)	
Hazard identification number	
Class	
Classification code	

Reason for revision: 3.2 Publication date: 2019-01-08
Date of revision: 2019-12-18

Revision number: 0001 Product number: 61330 11/14

14.4. Packing group	
Packing group	
Labels	
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	
Limited quantities	
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Appey II of MARROL 73/78	Not applicable, based on available data

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **European legislation:**

VOC content Directive 2010/75/EU

VOC content	Remark
97.10 %	
767.090 g/l	

Indicative occupational exposure limit values (Directive 98/24/EC, 2000/39/EC and 2009/161/EU)

2-butoxyethanol

Product name	Skin resorption
2-Butoxyethanol	Skin

Ingredients according to Regulation (EC) No 648/2004 and amendments

≥30% aliphatic hydrocarbons, <5% cationic surfactants

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Designation of the substance, of the group of substances or of the mixture • hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics • criteria for any of the following hazard classes Designation of the substance, of the group of conditions of restriction 1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of differ	and use of certain dangerous substances, mixtures and articles.		
		conditions of restriction	
or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.15 types A for F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1. (d) hazard class 5.1. (e) hazard class 5.1. (d) hazard class 5.1. (e) hazard class 5.1. (e) hazard class 5.1. (f) hazard class 5.1. (g) hazard class 5.1. (hazard class 6.1.) (hazard class 6.1.)	< 2% aromatics criteria for any of the following or categories set out in Annes (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2 types A and B, 2.9, 2.10, 2.12 1 and 2, 2.14 categories 1 and to F; (b) hazard classes 3.1 to 3.6, 2 effects on sexual function and development, 3.8 effects oth effects, 3.9 and 3.10; (c) hazard class 4.1;	- ornamental articles intended to produce light or colour effects by means of differer hases, for example in ornamental lamps and ashtrays, - tricks and jokes, - games for one or more participants, or any article intended to be used as such, ever mamental aspects, . Articles not complying with paragraph 1 shall not be placed on the market. . Shall not be placed on the market if they contain a colouring agent, unless required iscal reasons, or perfume, or both, if they: - can be used as fuel in decorative oil lamps for supply to the general public, and, - present an aspiration hazard and are labelled with H304, . Decorative oil lamps for supply to the general public shall not be placed on the mark niless they conform to the European Standard on Decorative oil lamps (EN 14059) add by the European Committee for Standardisation (CEN). . Without prejudice to the implementation of other Community provisions relating to lassification, packaging and labelling of dangerous substances and mixtures, suppliers insure, before the placing on the market, that the following requirements are met:) lamp oils, labelled with H304, intended for supply to the general public are visibly, le ind indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of hildren"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick amps — may lead to life- threatening lung damage";) grill lighter fluids, labelled with H304, intended for supply to the general public are ind indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lea fe threatening lung damage";) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are in a individual produced in a proportiate, grill lighter fluids and fuel for decorative lamps, labelled H304, intended for supply to the general public are in the proportiate, grill lighter fluids and fuel for decorative lamps, labelled H304, intended for supply to the general public and proportiate, grill lighter	

National legislation Belgium CHAIN CLEAN

No data available

Reason for revision: 3.2 Publication date: 2019-01-08 Date of revision: 2019-12-18

Revision number: 0001 Product number: 61330 12 / 14

2	
2-butoxy	/etnanoi

Résorption peau	2-Butoxyéthanol; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux,
	constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par
	présence de l'agent dans l'air.

National legislation The Netherlands

CHAIN CLEAN

Waterbezwaarlijkheid	B (2); Algemene Beoordelingsmethodiek (ABM)	
2-butoxyethanol		
Huidopname (wettelijk)	2-Butoxyethanol: H	

National legislation France

CHAIN CLEAN

No data available

۷:	<u>butoxyethanor</u>		
	Risque de pénétration	2-Butoxyéthanol; PP	
	percutanée		

National legislation Germany CHAIN CLEAN

	WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017	
h	hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
	TA-Luft	5.2.5/I	
2	2-butoxyethanol		
	TA-Luft	5.2.5	
	TRGS900 - Risiko der	2-Butoxyethanol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des	
	Fruchtschädigung	biologischen Grenzwertes nicht befürchtet zu werden	
	Hautresorptive Stoffe	2-Butoxyethanol; H; Hautresorptiv	

National legislation United Kingdom

CHAIN CLEAN

No data available

2-butoxyethanol

Skin absorption	2-Butoxyethanol; Sk	
-----------------	---------------------	--

Other relevant data

CHAIN CLEAN

No data available

2-butoxyethanol

IARC - classification	3; 2-butoxyethanol
TLV - Carcinogen	2-Butoxyethanol (EGBE); A3

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H-statements referred to under heading 3:

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

(*) INTERNAL CLASSIFICATION BY BIG

ADI Acceptable daily intake

AOEL Acceptable operator exposure level

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level DNEL Derived No Effect Level EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 % LD50 Lethal Dose 50 %

No Observed Adverse Effect Level NOAEL NOEC No Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic **PNEC Predicted No Effect Concentration** STP **Sludge Treatment Process**

vPvB very Persistent & very Bioaccumulative

Reason for revision: 3.2 Publication date: 2019-01-08 Date of revision: 2019-12-18

Revision number: 0001 Product number: 61330 13 / 14

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3.2 Publication date: 2019-01-08

Date of revision: 2019-12-18

Revision number: 0001 Product number: 61330 14 / 14